



# **ACTION-512**



## **DESCRIPTION**

ACTION-512 is a passive system designed to deliver a highly versatile solution, from fixed installations to the popular portable PA application. Its rotatable horn with 90° x 60° dispersion means the enclosure can be used horizontally in a fixed installation, as a stage monitor or even as front fill.

As part of our company culture, all our systems are developed under a single philosophy: to deliver the highest possible quality in terms of both materials and overall system design. In the ACTION-500 series we use the same birch plywood as our touring systems for a tight, natural warm sound found nowhere else on the market.

For long-term optimal performance of the ACTION-500 passive versions, the system can only be a complete sound system when rounded out with our amplifiers and processors with stored presets and limiters.

#### **KEY FEATURES**

- · Passive two-way system
- · Birch plywood enclosure
- · Durable ISO-flex paint
- · Recommended processor: DSP-226
- · Recommended amplifier: PA series

## **APPLICATIONS**

- · Live sound reinforcement
- · Bands, DJ's and performers
- · Speech and vocals
- $\cdot \, \text{Music playback in entertainment}$
- $\cdot$  A/V, conferences and presentations

#### **SPECIFICATIONS**

Performance		
Frequency Range (-10 dB)	50 Hz - 20 kHz	
Horizontal Coverage (-6 dB)	90°	
Vertical Coverage	60°	
Nominal Impedance	8 ohms	
RMS Power Handling	300 W	
Peak Power Handling	1200 W	
On-axis Sensitivity 1W/1 m	96 dB SPL	
Maximum Peak SPL at 1 m	131 dB	
Recommended Amplifier	PA-1500	
Recommended Processor	DSP-226	
Connectors		
Audio Input Connector	1 x speakON NL4	
Audio Output Connector	1 x speakON NL4	
Enclosure		
Enclosure Construction	Birch Plywood	
Enclosure Geometry	Trapezoidal	
Rigging	M10 Rigging Points	
Finish	ISO-flex Paint	
Color	Black	
Depth	380 mm (15,0 in)	
Dimensions ( H x W x D )	620 x 385 x 380 mm 24,4 x 15,2 x 15,0 in	



# **ACTION-512**

Net Weight	19,0 kg ( 41,8 lb )	
Components		
LF Driver	12MI	
HF Driver	M-34	
Horn/Waveguide	BC-916	
Shipping Carton Dimensions ( H x W x D )	690 x 435 x 435 mm 27,2 x 17,1 x 17,1 in	
Shipping Weight	21,0 kg ( 44,4 lb )	

# **ORDERING INFORMATION**

Model	Description	P/N	
System			
ACTION-512		10427246	
Replacement Part	ts		
12MI	Cone Transducer	10214310	
BC-916	Horn	30006590	
F-ACT512	Filter	30009291	
GM-12MI	Recone Kit	20208290	
GM-M34	Diaphragm	20205060	
M-34	Compression Driver	10207080	
Accessories			
ANL-2	Rigging Accessories	10101020	
AXF-X12	Installation & Stacking Acc.	10104831	
AXU-ACT512	Installation & Stacking Acc.	10104605	
FUN-VT12	Transport Accessories	10103710	
SPK4-1	Electronic Accessories	20502000	
SPK4-10	Electronic Accessories	20502001	
SPK4-20	Electronic Accessories	20502002	
TRD-6	Installation & Stacking Acc.	10104470	
TRD-7	Installation & Stacking Acc.	10104471	
TRPD-S2-PAK	Installation & Stacking Acc.	10104011	

#### **DIMENSIONS**









