artec 300 series



ARTEC-306-W



DESCRIPTION

The ARTEC-306-W 2-way passive full range loudspeaker utilizes a 6" low frequency transducer and the M-26 compression driver. The cabinet manufactured using top quality of Birch plywood and finished with a durable white paint finish. Thanks to its small size, it is ideal for venues with low ceilings, or limited space.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

A rotatable horn allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics. The cabinet is delivered with a U-bracket mount.

KEY FEATURES

- ·1 x 6B low frequency loudspeaker
- ·1 x M-26 compression driver
- · Rotatable 90° x 60° horn
- · Vertical or horizontal positioning
- · VESA75/VESA100 standard threaded mounting points
- · AXU-A306-W U-Bracket included

APPLICATIONS

- \cdot A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

SPECIFICATIONS

Performance		
Frequency Range (-10 dB)	70 Hz - 20 kHz	
Horizontal Coverage (-6 dB)	90°	
Vertical Coverage	60°	
Nominal Impedance	8 ohms	
RMS Power Handling	100 W	
Peak Power Handling	400 W	
On-axis Sensitivity 1W/1 m	90 dB SPL	
Maximum Peak SPL at 1 m	116 dB	
Recommended Amplifier	PA-900	
Recommended Processor	DSP-226	
Connectors		
Audio Input Connector	Covered Barrier Strip Terminals	
Audio Output Connector	Covered Barrier Strip Terminals	
Enclosure		
Enclosure Construction	Birch Plywood	
Enclosure Geometry	Trapezoidal	
Rigging	M10 Rigging Points	
Finish	ISO-flex Paint	
Color	White	
Depth	260 mm (10,2 in)	
Dimensions (H x W x D)	385 x 195 x 260 mm 15,2 x 7,7 x 10,2 in	
Net Weight	7,2 kg (15,8 lb)	



ARTEC-306-W

Components

LF Driver	6B	
HF Driver	M-26	
Horn/Waveguide	BCT-96	
Shipping	471 x 266 x 330 mm	
Carton Dimensions (H x W x D)	18,5 x 10,5 x 13,0 in	
Shipping Weight	9,2 kg (20,3 lb)	

ORDERING INFORMATION

Model	Description	P/N	
System			
ARTEC-306-W		10423851	
Replacement Parts			
6B	Cone Transducer	20208260	
BCT-96	Horn	30006201	
F-ACT8	Filter	30005424	
GM-M26	Diaphragm	20205050	
LAMP-F-18	Lamp	30000536	
M-26	Compression Driver	10207070	
Accessories			
ANL-2	Rigging Accessories	10101020	
AX-SPG1	Installation & Stacking Acc.	10105050	
AXC-AT	Installation & Stacking Acc.	10104310	
AXR-AR5-W	Installation & Stacking Acc.	10104880	
AXW-3-W	Installation & Stacking Acc.	10104860	

DIMENSIONS









