artec 300 series



ARTEC-310.64-W



DESCRIPTION

The ARTEC-310.64-W is a compact 2-way full-range loudspeaker system comprised of one 10" low frequency transducer and one M-34 compression driver with titanium diaphragm. The rotatable waveguide provides 60° x 40° coverage and allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

The cabinet is fitted with M10 threaded suspension points. Four VESA75/VESA100 standard threaded mounting points on the rear of the cabinet provide a secure fixing point for DAS mounting brackets. The cabinet is delivered with a U-bracket mount

KEY FEATURES

- ·1 x 10MI low frequency loudspeaker, 2.5" VCD
- ·1 x M-34 compression driver
- · VESA75/VESA100 standard threaded mounting points
- · Rotatable 60° x 40° (310.64) horns
- · Vertical or horizontal positioning
- · AXU-A310-W U-Bracket included

APPLICATIONS

- \cdot A/V systems and corporate events
- $\boldsymbol{\cdot}$ Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

SPECIFICATIONS

Performance		
Frequency Range (-10 dB)	60 Hz - 18 kHz	
Horizontal Coverage (-6 dB)	60°	
Vertical Coverage	40°	
Nominal Impedance	8 ohms	
RMS Power Handling	250 W	
Peak Power Handling	1000 W	
On-axis Sensitivity IW/I m	90 dB SPL	
Maximum Peak SPL at 1 m	126 dB	
Recommended Amplifier	PA-900	
Recommended Processor	DSP-226	
Connectors		
Audio Input Connector	Covered Barrier Strip Terminals	
Audio Output Connector	Covered Barrier Strip Terminals	
For Lance		
Enclosure		
Enclosure Construction	Birch Plywood	
Enclosure Geometry	Trapezoidal	
Rigging	M10 Rigging Points	
Finish	ISO-flex Paint	
Color	White	
Depth	345 mm (13,6 in)	
Dimensions (H x W x D)	610 x 295 x 345 mm 24,0 x 11,6 x 13,6 in	
Net Weight	15,5 kg (34,2 lb)	



ARTEC-310.64-W

Components

HF Driver	M-34	
Horn/Waveguide	BC-614	
Shipping Carton Dimensions (HxWxD)	705 x 391 x 416 mm 27,8 x 15,4 x 16,4 in	
Shipping Weight	19,5 kg (43,0 lb)	

ORDERING INFORMATION

Model	Description	P/N
System		
ARTEC-310.64-W		10423855
Replacement Parts		
BC-614	Horn	30006443
F-ACTI5	Filter	30005082
GM-10MI	Recone Kit	20208421
GM-M34	Diaphragm	20205060
LAMP-F-21	Lamp	30000535
M-34	Compression Driver	10207080
Accessories		
ANL-2	Rigging Accessories	10101020
AX-SPG1	Installation & Stacking Acc.	10105050
AXC-AT	Installation & Stacking Acc.	10104310
AXF-AR510-W	Installation & Stacking Acc.	10104830
AXR-AR5-W	Installation & Stacking Acc.	10104880
AXW-3-W	Installation & Stacking Acc.	10104860

DIMENSIONS









