artec 300 series



ARTEC-326-W



DESCRIPTION

The ARTEC-326W 2-way passive full range loudspeaker utilizes twin 6" low frequency transducer and the M-26 compression driver. The cabinet is manufactured using top quality Birch plywood and finished with a durable black paint finish. It is ideal for venues with low ceilings, or limited space when installed in the horizontal position.

The Artec-300 cabinets are constructed from Baltic Birch plywood and finished with a durable ISO-flex paint. The trapezoidal enclosure design helps eliminate standing wave coloration and at the same time, permits close-packed horizontal or vertical arrays.

A rotatable horn allows the systems to be installed in either the vertical or horizontal position maintaining the needed dispersion characteristics. The cabinet is delivered with a U-bracket mount.

KEY FEATURES

- · 2 x 6B low frequency loudspeakers
- ·1 x M-26 compression driver
- · Rotatable 90° x 60° horn
- · Vertical or horizontal positioning
- · VESA75/VESA100 standard threaded mounting points
- · AXU-A326-W U-Bracket included

APPLICATIONS

- \cdot A/V systems and corporate events
- · Meeting rooms, classrooms, and exhibit areas
- · Installations in bars and clubs

SPECIFICATIONS

Derformance

| Performance | |
|-----------------------------|--------------------------------------------|
| Frequency Range (-10 dB) | 60 Hz - 20 kHz |
| Horizontal Coverage (-6 dB) | 90° |
| Vertical Coverage | 60° |
| Nominal Impedance | 16 ohms |
| RMS Power Handling | 200 W |
| Peak Power Handling | 800 W |
| On-axis Sensitivity 1W/I m | 93 dB SPL |
| Maximum Peak SPL at 1 m | 122 dB |
| Recommended Amplifier | PA-900 |
| Recommended Processor | DSP-226 |
| Connectors | |
| Audio Input Connector | Covered Barrier Strip Terminals |
| Audio Output Connector | Covered Barrier Strip Terminals |
| Enclosure | |
| Enclosure Construction | Birch Plywood |
| Enclosure Geometry | Trapezoidal |
| Rigging | M10 Rigging Points |
| Finish | ISO-flex Paint |
| Color | White |
| Depth | 260 mm (10,2 in) |
| Dimensions (H x W x D) | 550 x 195 x 260 mm 21,7 x 7,7 x 10,2 in |
| Net Weight | 10,0 kg (22,1 lb) |



ARTEC-326-W

Components

| LF Driver | 6B | |
|----------------------------------------|---------------------------------------------|--|
| HF Driver | M-26 | |
| Horn/Waveguide | BCT-96 | |
| Shipping Carton Dimensions (H x W x D) | 638 x 266 x 330 mm 25,1 x 10,5 x 13,0 in | |
| Shipping Weight | 13,5 kg (29,8 lb) | |

ORDERING INFORMATION

| - CREEKING IN CRIMATION | | | |
|-------------------------|------------------------------|----------|--|
| Model | Description | P/N | |
| System | | | |
| ARTEC-326-W | | 10423852 | |
| ARTEC-320-W | | 10423832 | |
| Replacement Parts | 5 | | |
| 6B | Cone Transducer | 20208260 | |
| BCT-96 | Horn | 30006201 | |
| F-AR326 | Filter | 30006898 | |
| GM-M26 | Diaphragm | 20205050 | |
| LAMP-F-18 | Lamp | 30000536 | |
| M-26 | Compression Driver | 10207070 | |
| Accessories | | | |
| ANL-2 | Rigging Accessories | 10101020 | |
| AX-SPG1 | Installation & Stacking Acc. | 10105050 | |
| AXC-AT | Installation & Stacking Acc. | 10104310 | |
| AXR-AR5-W | Installation & Stacking Acc. | 10104880 | |
| AXW-3-W | Installation & Stacking Acc. | 10104860 | |

DIMENSIONS









