

INTEGRAL series



INTEGRAL-WA2



DESCRIPTION

INTEGRAL-WA2 is a 2-channel compact wall amplifier equipped with micro-SD card, USB, local line input and Bluetooth. Specially designed to be installed in the walls of commercial / educational facilities or domestic use.

It uses a high-efficiency class-D amplifier for a maximum power output of 2 x 25 W, at 4ohm. The buttons at the front panel allow volume control, input source selection, etc. A remote control is also included with the unit, as well, an electrical box of 86 x 86 mm.

KEY FEATURES

- 2 channel amplifier, wall-panel format
- 4 independent input sources
- 25 W per channel @ 4 ohms
- High Efficiency Class D topology
- Input Sources: Auxiliary Line, micro-SD card, USB and BlueTooth
- Universal Power Supply
- 86 x 86 electrical box included for easy installation
- Remote control included

APPLICATIONS

- Small Retail Stores
- Domestic
- Educational and meeting rooms

SPECIFICATIONS

Output Power Ratings

Power 8 Ohms, Both Channels Driven	2 x 12.5 W
Power 4 Ohms, Both Channels Driven	2 x 25 W

Electronics and Connectors

Amplifier Channels	2
Output Circuitry	Class D
Frequency Response	20 Hz - 20 kHz (+0 -0.5 dB)
Sensitivity	1.25 V (+4 dBu)
Voltage gain	18 dB
Controls	Push Buttons & Remote
Amplifier Protections	Short Circuit, DC Output
Audio Signal Input Connector	Terminal Block
Speaker Output Connector	Terminal Block
Current Draw 230 V / 115 V	0.3 A / 0.6 A

Dimensions-Weight

Dimensions (H x W x D)	86 x 86 x 36 mm 3,4 x 3,4 x 1,4 in
Net Weight	0,1 kg (0,1 lb)



ORDERING INFORMATION

Model	Description	P/N
System		
INTEGRAL-WA2		10721060

DIMENSIONS

