## TG-10CH2

Order No. 0252670

Charging station for transmitters TG-10T/1 and receivers TR-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

Supplied w/o devices.

Model	TG-10CH2
Suitable for	2 x TG-10T/1, TG-10R/1, KA-10
	components
Power supply	via encl. power supply
Dimensions	75 x 41 x 85 mm
Weight	485 g



## TG-10CH18

Transport case with integrated charging function, for transmitters TG-10T/1 and receivers TG-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of up to 18 devices
- · Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

Supplied w/o devices.

TG-10CH18
18 x TG-10T/1, TG-10R/1, KA-10
components
via encl. switch-mode power supply
361 x 422 x 189 mm
3.26 kg



## TG-64CH18

Order No. 0259620

Transport case with integrated charging **function,** for transmitters and receivers of the TG-98 series as well as the TG-16 series.

- For simultaneously charging rech. batteries of up to 18 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging
- Mechanical reverse polarity protection

Model	TG-64CH18
Description	transport case with charging
	function
Colour	black
Suitable for	18 x TG-98RA/5, TG-98TA/5, TG-
	16RA/1, TG-16TA/1
Power supply	via encl. switch-mode power supply
Dimensions	362 x 422 x 189 mm
Weight	3.3 kg

• Protection against overload, short-circuit and deep discharge

Supplied w/o devices.



## TG-10CH36

Order No. 0252680

Transport case with castors and integrated charging function, for transmitters TG-10T/1 and receivers TG-10R/1 as well as for KA-10 components.

- For simultaneously charging rech. batteries of up to 36 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 8 hours
- Each slot with LED for indicating battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge

Model	TG-10CH36
Suitable for	36 x TG-10T/1, TG-10R/1, KA-10
	components
Power supply	via encl. switch-mode power supply
Dimensions	400 x 561 x 230 mm
Weight	7.3 kg

- Robust hard-sided plastic transport case with carrying
- Due to the integrated telescopic handle and 4 castors, the transport case can easily be pulled like a trolley
- Can be locked via key

Supplied w/o devices.

