



## GM-5215LDU

Order No.: 0236310

### PRODUCTINFOS

#### Double gooseneck microphones with LED

- Back electret supercardioid cartridges
- High sensitivity
- 10 dB attenuator
- Low cut switch
- LED for indicating operating status
- Flexible positioning due to vertically adjustable goosenecks (160°)
- Common 3-pole XLR plug
- Operation via +48 V phantom power

### TECHNICAL SPECIFICATIONS

#### GM-5215LDU

|                     |                      |
|---------------------|----------------------|
| Description         | gooseneck microphone |
| Version             | double, LED          |
| Transmission method | cable                |

**GM-5215LDU**

|                                |                       |
|--------------------------------|-----------------------|
| Polar pattern                  | supercardioid         |
| System                         | back electret         |
| Audio frequency range          | 80-18,000 Hz          |
| Nominal impedance              | 220 Ω                 |
| Sensitivity                    | 16 mV/Pa              |
| Max. sound pressure            | 125 dB                |
| Power supply                   | DC 48 V phantom power |
| Admiss. ambient temp.          | 0-40 °C               |
| Dimensions                     | 492 mm                |
| Weight                         | 335 g                 |
| Connection                     | XLR, bal.             |
| Packing dimensions (W x H x L) | 0.095 x 0.06 x 0.66 m |
| Gross weight                   | 0.53 kg               |
| Net weight                     | 0.335 kg              |