

# LBB 1997/00 Plena Voice Alarm System Remote Control Extension

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Remote control of the Plena Voice Alarm System routers
- ▶ EN 54-16 certified and EN 60849 compliant
- ▶ Emergency (EMG) and background music (BGM) zone selections
- ▶ EMG state and fault indicators
- ▶ One extension per router

The Plena Voice Alarm System remote control panels allow the system to be controlled remotely from one or two remote locations. There are five models available:

- The fireman's panel, which has oversized, illuminated controls and an all-call function
- The main RC unit, which duplicates the front panel of the Plena Voice Alarm System Controller
- The RC extension, which duplicates the front panel of the router
- The main RC kit
- The RC extension kit

The kits are a functional match to the remote control and the RC extension, with connectors on the front panel instead of controls and indicators.

## Functions

The LBB 1997/00 extension duplicates the LBB 1992/00 Plena Voice Alarm System router front panel. One extension is needed per router, but not all routers need to have a remote control.

An LED meter shows the presence and level of the calls that are running in the system. The fault indicators show detailed information of any faults

present in the system. The unit connects to the Plena Voice Alarm System via standard shielded CAT 5 cable. The included rack mounting brackets can also mount the unit on a wall with spacing for cables at the back, as well as to a horizontal surface above or below the unit.

One or more extensions need to be connected to a voice alarm RC or voice alarm RC kit.

## Certifications and approvals

Safety	acc. to EN 60065
Immunity	acc. to EN 50130-4
Emission	acc. to EN 55103-1
Emergency	acc. to EN 54-16 / EN 60849

Region	Certification	
Europe	CE	Declaration of Conformity
	CPD	
	CPD	
Poland	CNBOP	

## Installation/configuration notes



LBB 1997/00 Rear view

## Parts included

Quantity	Component
1	LBB 1997/00 Remote Control Extension
1	Set of 19" mounting brackets
1	1 m CAT 5 cable

## Technical specifications

### Electrical\*

Power supply	
Voltage	24 VDC, +15% / -15%
Current typical	50 mA
Current max (indicator test)	200 mA (indicator test)
Relay contacts	30 V, 1 A

\* Technical performance data according to IEC 60268-3

### Mechanical

Dimensions (H x W x D)	88 x 430 x 90 mm (19 in wide, 2U high)
Weight	Approx. 2 kg
Mounting	Stand-alone, 19" rack
Color	Charcoal

### Environmental

Operating temperature	-10 °C to +55 °C (14 °F to +131 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	<95%

## Ordering information

### LBB 1997/00 Plena Voice Alarm System Remote Control Extension

A six-zone Plena Voice Alarm System router remote control.

Order number **LBB1997/00**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
12000 Portland Avenue South  
Burnsville MN 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
audiosupport@us.bosch.com  
www.boschsecurity.com

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security  
Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com