



NOISE REDUCTION MODULE

SMART TOUCH BUTTONS

ALUMINIUM ALLOY BODY

EXTRA MIC INPUT WITH 48V

SUPPORT UP TO 64GB



1 x 16GB SD CARD IS INCLUDED

FEATURES

- *Smart touch buttons, easy operation. With recording, playback control, mode, quantity switching and volume shortcut key.
- *With 4 meeting modes: FFIO, NORMAL, FREE, APPLY.
- *Spokesman quantity limitation: option for 1, 2, 4, 6. Chairman is not limited.
- *Support Max 32 pieces microphone units. Expandable up to 60 units.
- *Hand in hand cable connection way, easy for installation and maintain.
- *Adopt digital equalization module and noise reduction processing module for audio processing, to ensure clear and good sound quality. With 1 channel audio input and 1 channel audio output.
- *With 1 group original audio channel output, connect with amplifier.

- *With 1 group recording channel output, connect with external recording device.
- *Built-in recording function and SD interface, can record meeting conversation.
- *Can connect external mic, gain is adjustable.
- *With 48V Phantom power can be controlled, connect with external mic, gain is adjustable.
- *Support 24V DC power supply, for the controller and mic units.
- *Control unit shell adopt metallic material, both shell and cables has the connection with ground line, to ensure the function of antistatic 6000V.
- *Delicate desktop design, easy for operation.
- *With 3.5mm headphone jack, monitoring meeting conversation.

Model	CCU-131
Microphone Quantity	≤30
Frequency Response	30Hz ~ 20KHz
SNR	>75 dB(A)
Dynamic Range	>80 dB
Crosstalk	>80 dB
THD	<0.05%
Power Supply	24V DC
Audio Input	LINE IN : 350mV Balance
Audio Output	LINE OUT 1: 1V Balance
Output Load	>1KΩ
Static Consumption	10W
Output Consumption	70W
Connector	8 core aviation plug
Standards	IEC60914
Working Temperature	-10°C~+60°C
Working Humidity	20%~80% relative humidity, without condensation
Color	Black
Dimension(mm)	210(L)×132(W)×50(H)
Weight	1.65kg