



### FEATURES

- \*With new digital design.
- \*With ring-shaped speech indicator light that can show the status of speech. Red light stands for speaking, green light stands for waiting for a speech.
- \*The special designed microphone shield can eliminate the "poop-poop" low frequency sound even without using the windproof cotton cover.
- \*The chairman is unrestricted by microphone modes and number of speakers.
- \*The chairman unit has full-control priority and can be placed in any position of the loop. The units adopt hand-in-hand cascade connection mode, convenient for installation and maintenance.
- \*The reelable condenser microphone pole and professional large heart-shaped condenser microphones core make the unit a high sensitivity and intelligibility of the speech.
- \*The microphone has high and adjustable sensitivity.
- \*The power of the units is supplied by system host at 24V safe voltage.
- \*The units are connected by T-shaped 8-core cable.
- \*With two groups of 3.5mm stereo sound output socket, can be used for record and earphone connection.
- \*Built-in hi-fi speaker and volume control; with feedback inhibition function. The built-in hi-fi speaker will shut off automatically when the microphone is turned on.
- \*With discussion/automatic video-tracking function.

Model	CMC-18/CMD-18
Microphone Type	Heart shaped projection electrets microphone
Frequency Response	80Hz~16KHz
SNR	1KΩ
Dynamic Range	-46 dBV/Pa
Crosstalk	100dB(THD>3%)
THD	>80dB
Power Supply	>70dB
Audio Input	>80dB
Audio Output	<0.1%
Output Load	2W
Static Consumption	8-32Ω
Output Consumption	40mW maximum
Connector	3.5mm mono jack
Standards	IEC60914
Working Temperature	Built-in 1.8m aviation plug (8 core)
Working Humidity	Provided
Color	DC24V supplied by the host
Dimension(mm)	Black
Weight	0.86kg