


## **D6802/D6803      2.4G Digital Wireless Conference System Microphones**



### *Features*

- Using latest numerical control technology design.
- Condenser pick-up, provides the top definition and directivity
- LCD screen indicate working mode
- Use 1.5V AA \*3 battery and rechargeable lithium battery, convenient to change battery
- Speech number at the same time mostly 4 people, include chairman unit and delegate unit totally
- Standby function

### *Description*


D6802 & D6803 are 2.4G digital wireless conference system microphones. D6802 is a chairman unit and D6803 is a delegate unit. It has high fidelity microphone head, condenser pickup head, provides the top definition and directivity, light ring display working condition. It has LCD screen display working condition and equip with prior-button to control delegate unit speak, press the button can be mandatory to cut off the delegate to speech. Use 1.5V AA battery, pay attention to distinguish the positive and negative when replace the battery.

## Specification

Mode	D6802/D6803	D6802L/D6803L
Power supply	Dry battery (1.5V AA*3)	Rechargeable lithium battery (DC4.5V)
Transmitter power	10mW	10mW
Microphone core	Condenser, single direction	Condenser, single direction
Sensitivity	-43±2dB@1KHz	-43±2dB@1KHz
Frequency response	20Hz~18KHz	20Hz~18KHz
Power consumption	130mA	130mA


## Appearance

### Chairman unit



1. microphone head
2. LCD screen
3. standby/speak key
4. chairman unit priority key
5. non-removable microphone

### Delegate unit



1. microphone head
2. LCD screen
3. Standby /spcak key
4. non-removable microphone